



## OzoneSystems

Disinfect your water naturally

- UV and CD Technology Options
- Lower Energy Consumption
- Convertible Power: 110-240 VAC/50-60 Hz
- Less Inventory Needed with Universal Power Supply
- Family of Ozonators Designed Specifically for the Hot Tub Environment



**BALBOA**  
water group

## More Flexibility with More Choices

The O<sub>3</sub>zone family of ozonators were designed by Balboa, the leader in reliability in spa controls for over 20 years. These compact sanitizers were created specifically to withstand the demanding environment of the hot tub. Take your choice of Corona Discharge (CD) or Ultraviolet (UV) technology and rest assured that you have a comprehensive and reliable source of naturally disinfecting ozone.

### O<sub>3</sub>zone Chip

Our new chip technology ozonator produces up to 20% more ozone than comparable models. A lower power draw represents a savings of up to 37% less energy and with twice the precious metals and twin emitters, it is one reliable ozone generator.

### O<sub>3</sub>zone Cartridge

Our compact and polymer cartridge ozonator has a smaller footprint than most units and saves energy as well. It also features an extra fuse that protects from local failure and backs up the fuse on the controller board. This sealed unit is protected from harsh corroding environments and produces stable ozone output over a wide range of temperatures.

### O<sub>3</sub>zone UV Electronic Ballast

Our UV lamp ozone with PlasmaCell™ yields higher, consistent ozone levels using 1/3 the energy of conventional UV generators. In addition, the SmartStart™ solid-state electronic ballast eliminates start-up flicker, sputter, electronic noise and GFCI tripping.



## O<sub>3</sub>zone Family

Model	CD Cartridge	CD Chip	UV
Ozone (mg/hr @ 2 lpm)	75	50	30
Ozone (ppm)	390	250	125-163 (CE/UR)
Dimensions (inches)	5 x 6.375 x 2.67	5.5 x 7.5 x 3.0	12.75 x 2.4 x 2.78
Max Spa Size (gal)	1000	700	500
Amps (typical)	0.5	0.5	0.4
Power Usage (watts)	8.5	6.5	30
Housing	Plastic	Plastic	Plastic
Approvals	CUR/UR,CE,RoHS	CUR/UR,CE,RoHS	UR,CE
Power Supply (110-240 VAC 50/60 Hz)	Universal	Universal	Convertible
Warranty*	1 Year	1 Year	1 Year
Install Kit	Plastic Tubing, Check Valve, 4 Pin Amp Connector		

\* Ask your sales representative for warranty details.