



## SpaSuctions

Your Single Source Supplier

- Installation is fast and easy with only one single screw
- Passed rigorous impact and hair entrapment testing, under UL listing (SA8274)
- Available in different designs and colors for a custom look and fit
- Max Flow suction fittings rated to 124 gpm; Max Flow II rated to 200 gpm



## Achieve maximum flow while meeting UL safety requirements.

Unique design features make our Max Flow and Max Flow II suction fittings fast and easy to install while providing maximum flow rates and required safety features.

- UL listed (SA8274); passing rigorous impact and hair entrapment testing.
- Max Flow suction fittings rated to 124 gpm; Max Flow II rated to 200 gpm.
- The only fast and easy, single screw installation on the market.
- Only suction fittings available with Cyclone jet installation technology – compensating ring, “L” gasket and nut – providing good seal even with inconsistent wall thicknesses and eliminating the need for gluing; also available with flat gasket.
- Available with standard 2” or Balboa custom connections; the standard 2” connection can be assembled with any standard 2” fittings or pipe and meets all ASTM requirements; elbow, straight or tee adaptors can be specified with the Balboa Custom 2” connections.
- Available in light gray, silver, and dark gray. Contact a Balboa Water Group representative for custom colors or logo disk today.



### The Strength Of An Industry Leader

Balboa Water Group provides a full range of industry-leading products engineered to offer consistency, high quality and long service life. Our experienced staff can supply consulting, design, and manufacturing support to help you achieve a particular stylized appearance, provide new capabilities, or offer a more economical alternative. Our customer service and distribution centers are strategically located to offer you immediate and reliable service.